



## **SCORPION® ELECTRIC MONITOR**




- Allows for more effective use of personnel while reducing the potential risk of injury
- Efficient at high flows 4" fully -vaned waterway
- Extremely reliable system with built-in safety features:
  - Motors and control system components sealed to NEMA 4 rating
  - 10 vertical and 39 horizontal adjustable stop positions
  - Electronic controls with manual override
- Easy installation monitor comes with:
  - NEMA 4 rated connectors
  - NEMA 4 rated controller
- Optional one-button automatic stow with choice of stow position (up or down) and output signal type (pulse or continuous)
- Liquid-filled pressure gauge

SPECIFICATIONS							
Max. GPM (LPM)	2000 (7570)						
	Size	Туре					
Inlet	4"	150# ANSI Flange					
Outlet	3.5" NHT						
Controls	Electric						
Material/Finish	Elk-O-Lite® with						
	red urethane enamel						
Friction Loss	39 psi at 2000 gpm						
THEODIT LOSS	15 psi at 1250 gpm						
Travel	V -45° to +90° (135°)						
	H 347°						
Weight	Variable (see chart for specifics)						
Ratings and Certifications	CE						







## **Scorpion® Electric Selector Guide**

INLET SIZE/ TYPE	OUTLET SIZE	CONTROL MODULE VOLTAGE	MATERIALS	CERTIFICATIONS		
4" 150# ANSI Flange	3.5" NHT	12V DC	Elk-O-Lite®	CE	WEIGHT (Lbs.)	MODEL
S		0).03	•	•	43	8294-04
			1			Illustration

KEY s = standard o = option

COMPONENTS & OPTIONS		ILLUSTRATION	MODEL
Operator Controls	Panel Mount Controller	3	81339001
	Panel Mount Controller with Stow – adds stow button	5	81421001
	Aerial Switch Box Controller	2	81340001
	Joy Stick Controller – operator control	4	
	Hand-held remote control (includes receptacle)	6	81309001
Relay Control Box	Allows the monitor to interact with the operator control	9	81480001
Optional Control	Hand held control receptacle	7	81242001
24V Converter	24V to 12V		81093001
Auxiliary Battery Pack	Back-up to truck power (12V)	8	81466001
Companion Flange Kit	4" 150# ANSI steel flange with bolts and gaskets		81317001