



QUELL PRIVATE LIMITED

DISTRIBUTOR / AGENT FOR

FIRE FIGHTING AND LIFE SAVING EQUIPMENT

Block 51 Ayer Rajah Crescent #05-05 Singapore 139948

Email: quell@singnet.com.sg

Website: www.quell.com.sg

Tel: +65 6271 1918

Fax: +65 6273 1080



HIGH-RANGE TURBOJET NOZZLE MODEL: 1733



2 1/2" High-Range Turbo Jet Nozzle with Pistol Grip

Features

High-Range Turbojet Nozzles Features:

- Pattern Identification
- Larger more legible labels
- Simple to operate (1/4 turn from straight stream to fog)
- Raised lug marks straight stream for limited visibility operations
- Easy to service & repair
- Flow setting up to 250 GPM (950 LPM) at 100 psi (& bar) standard, 75 psi (5 bar) optional
- Compatible with Quick-Attack Foam Tube Style 770
- Replacement for style 1725 Turbojet nozzle

Applications/Solutions

- Engineered Solutions
- Fire OEMs
- Firefighting - Airport (ARFF)
- Firefighting - Industrial
- Firefighting - Structural
- Marine
- Mining
- Petro-Chemical



Turbojet Nozzle Specifications

Lightweight fog and straight stream nozzle with multiple fixed constant gallonage settings. The nozzle shall have spinning teeth, multiple pattern detents, a one piece solid rubber-like handle with dual handle stops, dual drive trunnions and an extruded Pyrolite body. The nozzle shall also have a minimum 110° angle at wide fog, a full-time swivel inlet, come with a ten year warranty, and capable of flushing without shutting down. Furthermore it meets all aspects of NFPA 1964.

Certification(s)



Warranty



Weight

6 3/4 lbs (3.1 kg)

Type

Selectable Gallonage

Material

Pyrolite

Brand

TurboJet

Swivel Inlet

2 1/2" (65 mm)

Length

11 1/2" (292 mm)

Flow (LPM)

475-550-750-950