

NORFOLK

Carbon Dioxide is tested on class B (flammable liquid) fires and is used as a clean extinguishing agent.

Features



- ❖ CE-marked in accordance with the PED
- ❖ Certified to EN1866
- ❖ Wheel marked in accordance with the MED
- ❖ Colour coded labels
- ❖ Quality steel cylinders
- ❖ Safe and reliable
- ❖ Quality assured for long service life
- ❖ Manufactured in Great Britain

Britannia Fire reserve the right to alter the specification of the product without prior notice



Technical Specification

Model	Capacity (Kg)	Full Weight (Kgs)	Temp Range	Operating Pressure (Bar) @ 20°C	Discharge Duration (Secs)	Discharge Range (M)	Width (mm)	Depth (mm)	Height (mm)
NWC20	20	82	-20° to + 60°C	50	44	4	435	420	1290

ADDITIONAL SPECIFICATIONS

Operating Pressure @ 20°C	50bar
Test Pressure (PT)	250bar
Maximum Allowable Pressure (PS)	169.3bar
Cylinder Material	Chromium molybdenum alloy steel
Screw down valve material	Brass
Ball valve material	Zinc plated steel

Cylinder Material	Chromium Molybdenum alloy steel
Screw down valve material	Brass
Ball valve material	Zinc plated steel
Hose	Synthetic rubber reinforced with high tensile wire braid
Finish	Polyester Powder Paint
Empty Weight	62kg

COMPONENT PARTS

ITEM	DESCRIPTION	PART No.
A	Trolley	TNWC20
B	Screw down valve	VLV0035
C	Red Fibre Washer	NRH0166
D	Discharge Hose Assy	HS0205
E	3/8" x 1/2" M/M Adapter	HS0310
F	3/8" Dowty Seal	HS0312
G	3/8" HP Ball Valve	EHV38
H	Nozzle (Internal)	RAM0131
I	Snow Horn	RAM0130
J	Syphon Tube (Internal)	TUBE0220
K	Cylinder	CYL0220
-	Pull Tight Seal (not shown)	BRH0175

Tel +44 (0)1508 488416