



QUELL PRIVATE LIMITED

DISTRIBUTOR / AGENT FOR

FIRE FIGHTING AND LIFE SAVING EQUIPMENT

Block 51 Ayer Rajah Crescent #05-05 Singapore 139948

Email: quell@singnet.com.sg

Tel: +65 6271 1918

Website: www.quell.com.sg

Fax: +65 6273 1080



SYNTEX 500 WHITE TYPE 1



Germanischer
Lloyd



DIN 14540:2007



Wheelmark

Construction

- 100% High tenacity polyester yarn, circular-woven (reinforcement)
- Circular woven twill weave, warp threads multiple twisted
- High quality, very light synthetic rubber on the basis of EPDM Features
- Absolute tough, durable & very abrasion resistant
- Seawater resistant, weather resistant
- Aging and ozone resistant
- Temperature range -40 °C up to +100 °C
- Minimum friction loss because of very smooth inner lining
- Light and flexible
- Suitable for sea water, hot water and many chemicals

DIAMETER	WORKING PRESSURE	BURSTING PRESSURE	WEIGHT	APPROVALS	PART NO
38MM / 1.5"	16BAR	60BAR	210G	  	HO-TI-SSO-15
45MM / 1.75"	16BAR	60BAR	240G	  	HO-TI-SSO-17
52MM / 2.0"	16BAR	60BAR	290G	  	HO-TI-SSO-20
65MM / 2.5"	16BAR	60BAR	365G		HO-TI-SSO-25
70MM / 2.75"	16BAR	60BAR	395G		HO-TI-SSO-27
75MM / 3.0"	16BAR	60BAR	475G		HO-TI-SSO-30