



HANDLINE NOZZLES

SOLID STRIKE™

HANDLINE NOZZLES

1-23

Solid Strike™

The Solid Strike™ offers unsurpassed flow performance with flexibility that allows the nozzleman to vary GPM or reach without shutting down to change tip size. Unlike a traditional smooth bore tip, the Solid Strike™ utilizes the hydraulic forces of the water flow itself to converge and project a perfect solid stream of water at near identical exit velocity — maximizing the stable range of the stream. The Solid Strike™ operates like any traditional smooth bore tip on a shut-off, except that the nozzleman has the ability to vary the effective tip size under flow.

Features include:

- Dual construction free swivel/swivel for superior inlet movement and rotation
- Hard anodized, Teflon® impregnated aluminum alloy body and pistol grip
- Aluminum/bronze shut-off handle
- Delrin® adjustable hydrofoil
- Maximum operating pressure 200 psi

Tactile detents at flow setting equivalents to 3/4", 7/8", and 1" smooth bore

Integrated stream shaper

Dual drive shut-off

Ultra-reflective color coding



Twist-and-click tip exposes leader thread — to extend the hose line

British Standard Parallel Pipe (BSPP) base options available.

INLET SIZE	OUTLET SIZE	FLOW RATES*	HANDLE	MODEL
		GPM (LPM)	Horseshoe	
1.5"	1.5"	118/159/209 (447/602/791)	s	SS-475-GAAT

* Flow rate for each detent (3/4", 7/8", and 1") setting @ 50 psi (3.45 bar)

OPTIONS COLORS

silver	red	orange	yellow	green	blue
--------	-----	--------	--------	-------	------

Solid Strike® nozzle comes standard with chrome handle and natural Elk-O-Lite® pistol grip. Ultra-reflective, durable vinyl color coding bands are supplied with each nozzle. See above for colors.

THREADS

All nozzles are NHT unless otherwise specified. See index T-13 for optional base threads, including British instantaneous.