

Ball Shut-offs & Playpipes

Elkhart Brass Ball Shut-offs and Playpipes are designed and constructed for rugged use and reliable performance as well as an excellent foundation for your break-apart nozzle needs using either smooth bore or fog nozzles. Elkhart Brass Ball Shut-offs and Playpipes are available with a variety of options, including built-in smooth bores which can be used with a fog nozzle tip for maximum versatility.



British Standard Parallel Pipe (BSPP) and British Instantaneous (BS336) base options available.

HANDLINE NOZZLES



BALL SHUT-OFFS & PLAYPIPES

HANDLINE NOZZLES

1-25

BALL SHUT-OFFS & PLAYPIPES

Inlet Size	Outlet Size	WATERWAY SIZE				AVAILABLE INTEGRAL SMOOTH BORE DISCHARGE SIZE				BALL TYPES			SEAT		DRIVE	GRIP			BASE			HANDLE		MATERIAL		MODEL	FIGURE						
		1"	1 3/8"	1 1/2"	1 3/4"	1/2"	7/8"	15/16"	1"	1 1/8"	1 1/4"	Single Cutaway	Double Cutaway	Full Round		Single Adjustable	Double Non-Adjustable	Single	Double	Pistol Grip	Playpipe	Ladderhook	TYPE		LENGTH			Tab	Horseshoe	Brass	Elk-O-Lite®		
																							Rigid	Swivel	Free Swivel							Long	Short
1"	1"	•											S		•		•					S	O			S	O	•		SB-275	2		
		•											S		•		•					O		S			S	O		•	SB-275-A	2	
		•				•							S		•		•					O		S			S	O	•		SB-275-AT	1	
		•											S		•		•	•				O		S			S	O	•		SB-275-G	2	
		•											S		•		•	•				O		S			S	O		•	SB-275-GA	2	
		•				•							S		•		•	•				O		S			S	O		•	SB-275-GAT	1	
1.5"	1.5"	•											S		•		•					O	S	O			O	S	•		LB-275	2	
		•											S		•		•					O	S	O			O	S		•	LB-275-A	2	
		•											S		•		•	•				O	O	S			O	S		•	LB-275-GA	2	
			•										S		•		•					O	S	O			O	S	•		B-275	2	
			•										S		•		•		•			O	S	O			O	S		•	B-275-A	2	
			•										S	O	O		•	•					O	S			O	S		•	B-275-GA	2	
			•										S	O	O		•	•	•				O	S			O	S		•	B-375-A	2	
			•				•	•	•	•	•	S	O	O		•	•	•					O	S			O	S		•	B-375-AT	1	
			•										S	O	O		•	•	•				O	S			O	S		•	B-375-GA	2	
			•				•	•	•	•	•	S	O	O		•	•	•					O	S			O	S		•	B-375-GAT	1	
2.5"	1.5"		•									S		•		•					O	S	O			O	S	•		DB-275			
			•									S		•		•					O	S	O	S	O	O	S		•	DB-275-A			
			•									S		•		•	•				O	O	S	S	O	O	S		•	DB-275-GA			
			•									S	O	O		•	•						S	S	O	O	S		•	DB-375-A			
			•									S	O	O		•	•	•					S	S	O	O	S		•	DB-375-GA			
			•				•	•	•	•	•	S	O	O		•	•	•					S	S	O	O	S		•	DB-375-AT			
			•				•	•	•	•	•	S	O	O		•	•	•					S	S	O	O	S		•	DB-375-GAT			
			•									S			•		•		•				S			S		•	B-278	4			
			•									S			•		•		•				S			S		•	B-278-AT	4			
			•									S			•		•		•	•			S			S		•	B-278-L	4			
			•									S			•		•		•				S			S		•	B-877-A*				
				•								S			•		•		•	•		S						•	279-L	3			
				•								S			•		•		•	•				S				•	279-LA	3			
												S			•		•		•			S						•	211T				
2.5"	2.5"				•						S		•		•		•				S					S	•		JB-275				
					•						S		•		•		•						S			S		•	JB-275-A				
					•						S		•		•		•		•					S			S		•	JB-275-GA			

Key s = standard o = option

*B-278 (without ladderhook) + ST-190-BA (Triple Stack Tip)

BALL SHUT-OFFS AND PLAYPIPES CONFIGURATIONS

Figure 1	 INTEGRAL SMOOTH BORE (Shown with optional pistol grip) <i>Fig. 1</i>
Figure 2	 TYPICAL BALL SHUT-OFF (Shown with optional pistol grip) <i>Fig. 2</i>
Figure 3	 PLAYPIPE WITHOUT SHUT-OFF <i>Fig. 3</i>
Figure 4	 PLAYPIPE WITH SHUT-OFF <i>Fig. 4</i>

Figures depict general product types only and are not intended to be inclusive of all product features.

DOUBLE CUT-AWAY

Ball is hydraulically balanced for a smooth transition from closed to open and open to closed.

FULL ROUND

Ball has a solid bore for optimal flow characteristics and stream quality — particularly for smooth bores and shut-offs with built-in smooth bores.

SINGLE CUT-AWAY

Combines the features of smooth operation and excellent stream quality.

OPTIONS

COLORS

black	red	orange	yellow	Glow	green	blue
-------	-----	--------	--------	------	-------	------

Color options available for pistol grip and handle. Ball shut-offs standards are a rough chrome handle and natural Elk-O-Lite® pistol grip.

HANDLES

TAB



HORSESHOE



THREADS

All nozzles are NHT unless otherwise specified. See index T-13 for optional base threads, including British instantaneous.